



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **07012090 A**(43) Date of publication of application: **17.01.95**(51) Int. Cl. **F04D 27/02**(21) Application number: **05182055**(71) Applicant: **MITSUBISHI HEAVY IND LTD**(22) Date of filing: **28.06.93**(72) Inventor: **KAWASHIMA YASUHIRO****(54) SURGING GENERATION PREVENTIVE METHOD FOR COMPRESSOR****(57) Abstract:**

PURPOSE: To surely prevent generation of surging by finding a suction flow rate corresponding to gas molecular weight according to a polytropic head value assumed from an outside diametrical dimension or the rotating speed or the like of an compressor impeller.

CONSTITUTION: Impeller rotating speed of a compressor 1 is supplied to a polytropic computing element 22 from a speed indicator 24 arranged in a driving machine 2. A thermometer 26 is arranged in a gas suction side passage of the compressor 1, and a suction gas temperature T_s is supplied to a molecular weight computing element 23. On the other hand, a thermometer 28 is arranged in a gas delivery side passage, and a delivery gas temperature T_d is supplied to the molecular weight computing element 23. Suction pressure P_s or delivery pressure P_d is also supplied to the molecular weight computing element 23. A surging preventive controller 21 carries out operation to correct a polytropic head value according to respective measured data, and finds a suction flow

rate Q_s according to gas molecular weight. A signal is generated from a flow rate controller 17 according to the suction gas flow rate Q_s , and a control valve 12 is driven through an electropneumatic converter 13, and generation of surging is avoided.

COPYRIGHT: (C)1995,JPO

